

## EPOXY SYSTEM

### CHARACTERISTICS

ULK CHIM-1 is an Epoxy system suitable for application on marble slabs' front with high transparency and shiny characteristics.

Epoxy resin and cycloaliphatic amines-based system with PHR 100: 50 and low viscosity.

Epoxy resin system ideal for coloured marble, PHR 100:50. Fast adhesion product, it can be used in both oven and manual resining process of marble.

It gives you very good result on filling into microholes and microcracks.



**FEATURES**  
Epoxy resin



**COLOUR**  
transparent



**TYPE**  
liquid



**CONTAINER**  
ADR



### APPLICATION


Before applying the product, clean and slightly rough the surfaces to be glued. Mix thoroughly component A and component B with 100:50 ratio until reaching a homogeneous blend (we suggest to weigh exactly the quantity of part A and part B to use before mixing them).

The mixture obtained can be processed up to a maximum of 30'.

From the application: workable after 24 hours. After 7 days of application, the compound achieves maximum stability.

Caution: heat accelerates the hardening of the mixture, while the cold slows it down considerably. Do not put the mixed product inside the jars once the application is over. Close the containers well. Test before use. Observe the percentage between the two parts indicated. Cannot be used at temperatures below 10 ° C.

### APPLICATION MATERIAL



Marble

### PACKAGING:

1,500 KGS	20 KGS	200 KG	1000 KG
-----------	--------	--------	---------



This sheet cannot be reproduced or changed in any of its parts without permission of Global Shipping S.p.a.Unipersonale.

