

FLUID KRISTAL MASTIC

DESCRIPTION

Clear, low viscosity fluid mastic. Ideal for gluing and for horizontal repairs of marble, onyx and stone. The hardened product is already shiny. The low temperature reactivity is excellent. The adhesion on the materials and the mechanical resistance represent the outstanding qualities of this product

INSTRUCTIONS FOR USE

Be sure that surface that you must treat is dry, clean and free of dust. Take out the necessary mastic quantity from the tin / can / drum and the liquid hardener. Mix energetically and use the obtained product for your purposes. Do not put the unused final mixture again into the tin. If it is necessary to correct the product colour, use specific colored pasts or metal oxides. Add the colour before adding the hardener until you reach the desired hue and finally you can add the hardener. Any excess of colour can affect the final characteristics of the mastic. Take care. Keep the tins well closed after usage. Keep the mastic and the hardener far away from light sources and foremost far away from sun rays.



TECHNICAL DATA

| | |
|---|----------------|
| ASPECT | Clear liquid |
| DENSITY AT 25° C gr/cm ³ | 1.07 |
| COLOR | Kristal |
| RATIO OF USE WITH GLUE/HARDENER | 100+1,5/2,5 |
| GEL TIME IN BULK AT 25°C IN MIN | 6-8 |
| SHELF LIFE | 6 months |
| WORKING TIME SUGGESTED AT 25° C IN MIN APPROX | 2:45 -3:30 hrs |

This sheet cannot be reproduced or changed in any of its parts without permission of Global Shipping S.p.a. Unipersonale.

For the Safety rules please have a look at our data sheet.

The data in this sheet are based on our best experience and indicative only.

