

## ACRYLIC LACQUER THINNER

### DESCRIPTION

MULTICRYL ACRYLIC LACQUER THINNER is an innovative nitro thinner export suitable for thinning primers for usage on wood and iron. It's recommended item also for washing painting tools. 100 % Made in Italy.

### INSTRUCTIONS FOR USE

It can be used to dilute enamel, bottom and antirust, add nitro thinner in order to give to the vanishing product the required fluidity. Dilute the paint product until it reaches the disired fluidity. An exact dilution optimize the brightness of varnishing product. It can be used by immersion, with a brush or a print.

### IMPORTANT :

Always try an initial test before use.

This product is highly flammable and it is only for professional use.



### TECHNICAL DATA

|                                       |                         |
|---------------------------------------|-------------------------|
| PHYSICAL STATE AT 20°C                | Liquid                  |
| ODOUR                                 | Solvent                 |
| COLOR                                 | Colourless              |
| DENSITY AT 20°C                       | 821,2 kg/m <sup>3</sup> |
| BOILING POINT AT ATMOSPHERIC PRESSURE | 75 °C                   |
| FLASH POINT                           | -2 °C                   |
| MELTING POINT                         | --                      |
| SHELF LIFE                            | 6 Months                |

This sheet cannot be reproduced or changed in any of its parts without permission of Global Shipping S.p.a. Unipersonale.

For the Safety rules please have a look at our safety data sheet.

Please note: the data in this sheet are based on our best experience and indicative only.

