

## THIXOTROPIC EPOXY RESIN AND CYCLOALIPHATIC AMINES-BASED SYSTEM

### CHARACTERISTICS

ULK K-050 is fully featured among the latest epoxy generation with exceptional physical and chemical characteristics. It can be used on either light or white stones due to its remarkable UV and yellowing resistance. Easy colouring for use on dark and coloured stones. Suitable for vertical joints; minimal shrinkage during hardening process and excellent fatigue resistance. Recommended for bonding and outdoors applications due to its high weather resistance.



#### FEATURES

excellent resistance



#### COLOUR

ice white



#### TYPE

gel



#### CONTAINER

ADR



### APPLICATION

The surface, that has to be glued, has to be clean and slightly rough before the application. Mix component A with component B until obtaining a homogeneous blend. The mixture obtained must be used within 20-30 minutes. The surface will be walkable after 24 hours. The compound can not be used below 5° C and is suggests to observe the percentage between the two component A and B with 100:50 ratio. Don't put the mixed product inside the jar.

### APPLICATION MATERIAL



Granite



Marble



Natural stone



Ceramic



Metals



Glass

### APPLICATION TOOLS



spatula

### WHERE TO APPLY ?



indoor



outdoor

### PACKAGING:

1,5 KG	2,25 KG
A 1KG + B 0,5KG	A 1,5KG + B 0,75KG

### FAQ:

POT LIFE	SHELF LIFE
20-30 minutes	1 year

This sheet cannot be reproduced or changed in any of its parts without permission of Global Shipping S.p.a. Unipersonale.

