

EPOXY SYSTEM

CHARACTERISTICS

ULK CHIM-20 is a Bi-component epoxy system without solvent with low viscosity and medium reactivity. Suitable for the surface treatment and the consolidation of coloured marbles, granites and natural stones, it is recommended when the colour of the material needs to be considerably enhanced. Resin : Hardener 100: 33



FEATURES
Epoxy resin



COLOUR
transparent



TYPE
liquid



CONTAINER
ADR



APPLICATION


The two components must be carefully weighed and mixed until a homogeneous system is obtained. If possible, try to avoid the entrapment of air bubbles during mixing. After withdrawal, the containers must be hermetically closed.

The surface of the stone must be dried and clean. Hardening process is optimal at around 40°C.

If stored in original containers in dry and clean environment, the product can be used up to 1 year from production date. The product should never be exposed to direct sunlight. In case of crystallization, heat the product until the original transparency is achieved and, after mixing, return it back to standard ambient conditions.

The product must be always used in aerated ambient wearing the suitable Personal Protective Equipment. Before use, Material Safety Data Sheets must be carefully looked up.

APPLICATION MATERIAL



Marble

PACKAGING:

1,330 KGS	20 KGS	200 KG	1000 KG
-----------	--------	--------	---------

This sheet cannot be reproduced or changed in any of its parts without permission of Global Shipping S.p.a.Unipersonale.

