

EPOXY SYSTEM

CHARACTERISTICS

ULK CHIM-5 Bi-component epoxy system with very high viscosity and reactivity. Especially recommended for the surface treatment of natural stones when the original colour has to be preserved. Epoxy system suitable for application on slabs' front, high transparency.



FEATURES
Epoxy resin



COLOUR
transparent



TYPE
liquid




CONTAINER
ADR

APPLICATION

Before applying the product, clean and slightly rough the surfaces to be glued. Mix thoroughly component A and component B with 100:30 ratio until reaching a homogeneous blend (we suggest to weigh exactly the quantity of part A and part B to use before mixing them). The mixture obtained can be processed up to a maximum of 30'. From the application: workable after 24 hours. After 7 days of application, the compound achieves maximum stability. Caution: heat accelerates the hardening of the mixture, while the cold slows it down considerably. Do not put the mixed product inside the jars once the application is over. Close the containers well. Test before use. Observe the percentage between the two parts indicated. Cannot be used at temperatures below 10 ° C.

APPLICATION MATERIAL



Natural Stones

PACKAGING:

1,330 KGS	20 KGS	200 KG	1000 KG
-----------	--------	--------	---------

This sheet cannot be reproduced or changed in any of its parts without permission of Global Shipping S.p.a.Unipersonale.

