

## SEMIRAPID EPOXY SYSTEM, HIGH TRANSPARENCY

### CHARACTERISTICS

Epoxy resin and cycloaliphatic amines based system, ULK 505 has the advantage to be fast hardening while maintaining good transparency after curing, compared to other epoxy systems. Self-levelling; after application, the treated surface is ready to be used and walked in short time.



#### FEATURES

fast hardening



#### COLOUR

transparent



#### TYPE

liquid



#### CONTAINER


ADR



### APPLICATION

Before applying the product, clean and slightly rough the surfaces to be glued. Mix thoroughly component A and component B with 100:50 ratio until reaching a homogeneous blend (we suggest to weigh exactly the quantity of part A and part B to use before mixing them). The mixture obtained can be processed up to a maximum of 10-15'. From the application: workable after 24 hours. After 7 days of application, the compound achieves maximum stability. Caution: heat accelerates the hardening of the mixture, while the cold slows it down considerably. Do not put the mixed product inside the jars once the application is over. Close the containers well. Test before use. Observe the percentage between the two parts indicated. Cannot be used at temperatures below 10 ° C.

### APPLICATION MATERIAL



Granite



Marble



Natural stone



Ceramic



Metals



Glass

### PACKAGING:

1,5 KG

A 1KG + B 0,5KG

### FAQ:

SHELF LIFE

1 year

This sheet cannot be reproduced or changed in any of its parts without permission of Global Shipping S.p.a. Unipersonale.

