

SOLID KRISTAL MASTIC

DESCRIPTION

High viscosity solid mastic. It is used to glue and repair vertical marble, onyx and stone. The hardened product is already shiny. The low temperature reactivity is excellent. The adhesion to materials and excellent mechanical characteristics represents the outstanding qualities of this product.

INSTRUCTIONS FOR USE

Be sure that surface that you must treat is dry, clean and free of dust. Take out the necessary mastic quantity from the tin / can / drum and the liquid hardener. Mix energetically and use the obtained product for your purposes. Do not put the unused final mixture again into the tin. If it is necessary to correct the product colour, use specific-colored pasts or metal oxides. Add the colour before adding the hardener until you reach the desired hue and finally you can add the hardener. Any excess of colour can affect the final characteristics of the mastic. Take care.

Keep the tins well closed after usage. Keep the mastic and the hardener far away from light sources and foremost far away from sun rays.



TECHNICAL DATA

ASPECT	Opaque solid paste
DENSITY AT 25° C gr/cm ³	1.07
COLOR	Kristal
RATIO OF USE WITH GLUE/HARDENER	100+1,5/2,5
GEL TIME IN BULK AT 25°C IN MIN	6-8
SHELF LIFE	6 months
WORKING TIME SUGGESTED AT 25° C IN MIN APPROX	2:45 -3:30 hrs

This sheet cannot be reproduced or changed in any of its parts without permission of Global Shipping S.p.a. Unipersonale.

For the Safety rules please have a look at our data sheet.

The data in this sheet are based on our best experience and indicative only.

